COMBO WATER PEN









Ordering Code VZ8698AZ, 8698 meter VZ8699AZ, 8699 meter VZ8698PAZ, pH/EC probe for 8698 and 8699 VZ8698PAZ1,8698/99 extension cable-5M VP860101, empty bottle for cal. buffer storage

IP65 pH/EC/TDS/SALT/S.G/Temp. Pen

Hydroponics:8698

Aquaculture: 8699

- ■The world's first multifunctional water probe capable of measuring the conductivity range up to seawater salinity
- ■Auto ranging and integrated S.G. (Specific Gravity) and Salinity Unit for aquaculture users
- Clear LCD with backlight to display parameters in turns: PH, Conductivity, TDS, Salinity, S.G. and Temperature
- ■Replaceable sensor: rust-resisting EC and high quality pH
- Adjustable TDS factor for all hydroponic formula
- Multiple points calibration. EC/TDS/SALT: 4, pH:3

8698





ATC

Auto Temp. Compensation











8699

be	

pH range/resolution	0.00~14.00/resolution :0.01		
pH accuracy	+/-0.1		
EC (Auto range) 0~	199.9uS/cm, 200~1999uS/cm, 2.00~19.99mS/cm, 20.0~200.0mS/cm		
EC accuracy	+/-2% F.S +/- 1 digit		
EC resolution	0.1uS/cm, 1uS/cm, 0.01mS/cm, 0.1mS/cm		
TDS. Range(fis TDS factor)	0~199.9*f ppm, 200~1999*f ppm, 2.00~19.99*f ppt, 20.0~200.0*f ppt		
TDS. Accuracy/res.	+/-2% F.S +/- 1 digit;	res.:0.1,1ppm;0.01, 0.1ppt	
TDS Factor	0.40~1.00		
Salinity range		0.00~11.40ppt; 11.4~159.9ppt(NaCl)	
Salinity accuracy/res.		+/-2% F.S +/- 1 digit; res.:0.01 ppt, 0.1pp	
S.G. range		0.950~1.080 (NaCl)	
S.G. Resolution		0.001	
Temp. range	0.0~70.0°C(32.0~158.0°F)		
Temp. Accuracy/res.	+/-0.6°C; 0.1(+/-1°F; 0.1)		
ATC active range	0.0~50.0°C(32.0~122.0°F)		
Temp. Coefficient	2.0% per °C(1.1% per °F)		
Normalization Temp.	25.0°C (77°F)		
LCD size(mm)	30(H)x18(W)mm		
Operating temp.&RH9	% 0~50°C,	Humidity<80%	
Storage temp.&RH%	0~60°C,	Humidity < 90%	
Dimension(mm)	210(L)x39(W)x39(H)		
Weight	120g		
Battery	Built-in rechargeable lithium battery, 5V USB-C		
Power consumption	<6.5mA (backlight off),<12mA(backlight on)		
Response time	<90 seconds		
Sensor life time (with good maintenance)	> 6 months		
Standard Package	Standard Package Meter (with built-in bat.)/Manual/USB-C cable		

Optional accessory

-Empty vial for buffer storage(20mL)

-5M long extension cable kit

hard storage case/wrist strap



IP65 PH/EC/TDS/SALT/S.G/TEMP. PEN

In the past few decades, all pH and EC 2-in-1 meters designed for hydroponics were limited to measuring EC values up to 20 mS/cm. While this range is sufficient for measuring the nutrient solution used in hydroponic systems (typically between 0.5 and 5 mS/cm, rarely exceeding 10 mS/cm), it is not suitable for measuring the EC of seawater.

Seawater typically has an EC value of 50–55 mS/cm, far exceeding the 20 mS/cm limit of standard hydroponic meters. To accurately measure the EC of seawater, a specialized high-range EC meter is required, capable of measuring up to 200 mS/cm or higher.



Hydroponics Typically 0.5 ~5 mS/cm



Seawater typically has an EC value of 50–55 mS/cm

Specific Gravity (S.G.)

The concept of S.G. has been used for centuries in marine studies, earlier conductivity, making it a familiar metric for marine related field, such as aquariums, aquaculture systems, and desalination processes.

S.G. provides a practical approximation of salinity since seawater's salinity increases with higher S.G. For example: An S.G. of 1.023–1.025 corresponds to the typical salinity of 35 ppt in ocean water.

Salinity (SALT)

Salinity refers to the concentration of dissolved salts (mainly sodium chloride, NaCl) in seawater, typically expressed in ppt (parts per thousand). The average salinity of the world's oceans is approximately 35 ppt, meaning that each kilogram of seawater contains 35 grams of salt.

However, the salinity of the ocean varies due to regional environmental factors and natural processes. A salinity range between 30 ppt and 40 ppt is commonly observed.

